

Description

Premium calendered vinyl with high quality. No peeling and less than 2mm shrinkage at film edge.

Face film	Calendered PVC in Taiwan
Thickness	80 µm (3.2 mil) ±5%
Color and Finish	Gloss/Matt clear cover

Release liner

Single-PE coated silicone paper with Japan tech and highly quality.

Weight	80 gsm ±5%
Thickness	100 µm ±5%
Color and Finish	White with Graphictac design

Adhesive

Clear , permanent , solvent-based adhesive.

Type	Acrylic
Apply Temp.	+10°C ~ +40°C
Adhesion (20 min)	1300 g/25mm
Adhesion (24 hour)	1550 g/25mm
Cohesion	24 hours↑ with 1 kg loading

Application

Decoration , advertising in outdoor graphics. Suitable on curved apply. Printable with solvent-based , UV and Latex.

Shelf life & Storage condition

Shelf life is 3 years in original packaging, at 25°C and 50% relative humidity.

Length and Width

Length	45 or 50 meter
Width	0.94m(37inch)/1.295m(51 inch)/1.55m (61 inch)

Code	Description	Width
200-000	Glossy lamination	940/1295/1550
200-002	Semi-matte lamination	940/1295/1550
200-005	Matte lamination	940/1295/1550
200-250	Floor lamination (10 mil)	1295