

30 Series Frosted Window Film

Description

- ✓ Premium calendered PVC film with less shrinkage.
- ✓ No residue and yellowing after sticking and keeping 3 years without moving on the wall.

Face film	Calendered PVC in Taiwan
Thickness	100 µm (4 mil) ±5%
Color and Finish	9 colors with different embossing

Release liner

Single-PE coated silicone paper with Japan tech and high quality.

Weight	80 gsm ±5%
Thickness	110 µm ±5%
Color and Finish	White with Graphictac

Adhesive

Clear, permanent and solvent-based adhesive.

Type	Acrylic
Apply Temp.	+10°C ~ +40°C
Adhesion (20 min)	1200 g/25mm
Adhesion (24 hour)	1450 g/25mm
Cohesion	24 hours ↑ with 1 kg loading

Application

- ✓ Indoor and outdoor decorative designs for glass and window.
- ✓ Suitable for flat and curved surfaces.
- ✓ Also using for printing.
Ink compatibility: solvent, eco-solvent, latex and UV

Shelf life & Storage condition

Shelf life of 2 years in original packaging at 25°C and 50% relative humidity.

Durability

2 years for outdoor designs

Length and Width

Length	150ft / customized size
Width	0.92M (36.2 inch) / 1.27M (50 inch) / 1.524M (60 inch)

